



Cut - Precision Work



Dry Environment



The +

COVERPERF DURABILITY: ABRASION (exceptional wear resistance, >20,000 cycles) and WASHABILITY (performance guaranteed for up to 5 cycles at 30°C) for maximum durability

COVERPERF BREATHABILITY: Maximum breathability for optimal comfort

COVERPERF SKINCARE: Hypoallergenic to prevent irritation

Gauge 21 knit without fiberglass: Second skin feel for exceptional dexterity

Sandy nitrile palm coating: Excellent grip in dry and slightly oily environments

Long thumb-index reinforcement: Improved grip and prevents tearing for maximum durability

RCS: Integration of recycled materials (20%) to reduce environmental impact

HOT 1: Contact heat protection for hot parts 100°C / 15 sec

Touchscreen, Sanitized

DESCRIPTION

The CLAW CUT range is a new generation of cut-resistant gloves, designed to protect you in the most demanding tasks with a high level of cut resistance (from CUT D to A9) while providing excellent comfort and exceptional dexterity in all work environments (dry, wet, and oily).

The CLAW CUT D 400 model has been designed for fine handling work in dry and slightly oily conditions. The high gauge of 21 combined with an exceptionally soft and strong fiber (made of HPPE, recycled polyester, and spandex) provides a second-skin feel while offering excellent cut protection (CUT D).

The sandy nitrile coating and the long reinforcement between the thumb and index finger provide excellent grip and good handling. This coating ensures very good breathability (tested under the COVERPERF label) and also high abrasion resistance (COVERPERF label: >20,000 cycles).

CLAW CUT D 400 is made with recycled polyester fiber and is RCS certified (20% of the total product weight). It contains no fiberglass.

This glove is touchscreen compatible, allowing you to keep it on while using equipment with touch screens. The Sanitized treatment prevents the development of bacteria and odors, and the CLAW CUT D 400 is also hypoallergenic (COVERPERF SKINCARE test).

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CLD400006	6	10	100
1CLD400007	7	10	100
1CLD400008	8	10	100
1CLD400009	9	10	100
1CLD400010	10	10	100
1CLD400011	11	10	100

TECHNICAL FEATURES



Color	Black
Glove type	Seamless knitting
Coating level	Palm
Material of coating	Nitrile
Coating finition	Sandy
Reinforced part place	Between thumb and index finger
Reinforced part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0598/PPE/25/3573 Issue 1

Delivered by SGS Fimko Oy (0598) Takomotie 8 00380 HELSINKI Finland



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



4.X.4.2.D.

ANSI

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15



EN407:2020

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)



X.1.X.X.X

EN16350:2014

Protective gloves - Electrostatic properties

COVERPERF - Breathability

Gloves tested in a certified laboratory (CTC) offering excellent breathability. Removal of perspiration above 60mg/cm2/8h



COVERPERF - Durability/Abrasion resistance

Gloves tested in a certified laboratory (CTC) offering excellent resistance to abrasion. Resistance above 20 000 cycles, compared to 8000 cycles for standard EN 388



COVERPERF - Durability/Washable

MAJ 03/04/2026

