



Cut - Precision Work



DESCRIPTION

The CLAW CUT range is a new generation of cut-resistant gloves, designed to protect you in the most demanding tasks with a high level of cut resistance (from CUT D to A9) while providing excellent comfort and exceptional dexterity in all work environments (dry, wet, and oily).

The CLAW CUT F 400 model has been designed for fine handling work in dry and slightly oily conditions. The high gauge of 21 combined with an exceptionally soft and strong fiber (made from HPPE, recycled polyester, steel fiber, and spandex) provides a second-skin feel while offering maximum cut protection (CUT F, according to EN388 standards).

The sandy nitrile coating and the long reinforcement between the thumb and index finger provide excellent grip and good handling. This coating ensures very good breathability (tested under COVERPERF label).

CLAW CUT F 400 is made with recycled polyester fiber and certified RCS (18% of the total product weight). It contains no fiberglass.

This glove is touchscreen compatible, allowing you to keep it on while using equipment with touch screens.

Sanitized treatment: prevents the development of bacteria and odors, and the CLAW CUT F 400 is also hypoallergenic (COVERPERF SKINCARE).

Dry Environment



The +

- COVERPERF BREATHABILITY: Maximum breathability for optimal comfort
- COVERPERF DURABILITY: WASHABILITY (performance guaranteed for up to 5 cycles at 30°C) for maximum durability
- COVERPERF SKINCARE: Hypoallergenic to prevent irritation
- CUT F: Maximum cut protection level (EN388 standard)
- Gauge 21 knit without fiberglass: Second skin feel for exceptional dexterity
- Sandy nitrile palm coating: Excellent grip in dry and slightly oily environments
- Long thumb-index reinforcement: Improved grip and prevents tearing for maximum durability
- RCS: Integration of recycled materials (18%) to reduce environmental impact
- HOT 1: Heat protection from contact with hot parts up to 100°C / 15 sec
- Touchscreen, Sanitized

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CLF400006	6	10	100
1CLF400007	7	10	100
1CLF400008	8	10	100
1CLF400009	9	10	100
1CLF400010	10	10	100
1CLF400011	11	10	100
1CLF400012	12	10	100

SALES PACKAGING

TECHNICAL FEATURES



Gauge 21

Color	Black
Glove type	Seamless knitting
Coating level	Palm
Material of coating	Nitrile
Coating finition	Sandy
Reinforced part place	Between thumb and index finger
Reinforced part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0598/PPE/25/3575 Issue 1

Delivered by SGS Fimko Oy (0598) Takomotie 8 00380 HELSINKI Finland



EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



4.X.4.2.F.

ANSI

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15



EN407:2020

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)



X.1.X.X.X

EN16350:2014

Protective gloves - Electrostatic properties

COVERPERF - Breathability



COVERPERF -
Durability/Washable



COVERPERF - Skincare



MAJ 03/04/2026

