



16% RCS recycled polyester
Certified by Ecocert Greenlife 267872

Ref. 1CLF500

Cut - Precision Work



Oily Environment



The +

COVERPERF DURABILITY: WASHABILITY (performance guaranteed for up to 5 cycles at 40°C) for maximum durability
COVERPERF SKINCARE: Hypoallergenic to prevent irritation
CUT F: Maximum cut protection level (EN388 standard)
 21 Gauge Knit without fiberglass: Second skin feel for exceptional dexterity
 Double layer sandy finish nitrile palm coating: Excellent grip in dry and oily environments, waterproof
 Long thumb-index reinforcement: Improved grip and prevents tearing for maximum durability
RCS: Integration of recycled materials (16%) to reduce environmental impact
HOT 1: Contact heat protection 100°C / 15 sec.
 Touchscreen, Sanitized

DESCRIPTION

The CLAW CUT range is a new generation of cut-resistant gloves, designed to protect you in the most demanding tasks with a high level of cut resistance (from CUT D to A9) while providing excellent comfort and exceptional dexterity in all work environments (dry, wet, and oily).

The CLAW CUT F 500 model has been designed for fine handling work in dry and oily environments.

The high gauge of 21 combined with an exceptionally soft and strong fiber (based on HPPE, recycled polyester, steel fiber, and spandex) provides a second-skin feel while offering maximum cut protection (CUT F, according to EN388 standards).

The double-layer nitrile palm coating with a sandy finish is waterproof, and the long reinforcement between the thumb and index finger provides excellent grip and good handling in the most demanding dry and oily tasks.

CLAW CUT F 500 is made with recycled polyester fiber and certified RCS (16% of the total product weight). It contains no fiberglass.

This glove is touchscreen compatible, allowing you to keep it on while using equipment with touch screens.

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CLF500006	6	10	100
1CLF500007	7	10	100
1CLF500008	8	10	100
1CLF500009	9	10	100
1CLF500010	10	10	100
1CLF500011	11	10	100
1CLF500012	12	10	100

SALES PACKAGING

TECHNICAL FEATURES



Gauge 21

Color	Black
Glove type	Seamless knitting
Coating level	Palm
Material of coating	Nitrile
Coating finition	Smooth
Coating level	Palm
Material of coating	Nitrile
Coating finition 2	Sandy
Reinforced part place	Between thumb and index finger
Reinforced part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0598/PPE/25/3576 Issue 1

Delivered by SGS Fimko Oy (0598) Takomotie 8 00380 HELSINKI Finland



EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



4.X.4.2.F.

ANSI

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15



EN407:2020

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)



X.1.X.X.X

EN16350:2014

Protective gloves - Electrostatic properties

COVERPERF -
Durability/Abrasion resistance

COVERPERF -
Durability/Washable



COVERPERF - Skincare



MAJ 03/04/2026