



Cut - Precision Work



DESCRIPTION

The CLAW CUT range is a new generation of cut-resistant gloves designed to protect you in the most demanding tasks with a high level of cut resistance (from CUT D to A9) while providing excellent comfort and exceptional dexterity in all work environments (dry, wet, and oily).

The CLAW CUT F 505 model has been designed for fine handling work in dry and oily environments.

The high gauge of 18 combined with an exceptionally soft and strong fiber (based on HPPE, recycled polyester, steel fiber, and spandex) provides exceptional comfort while offering maximum cut protection (CUT F, according to EN388 standards).

The double-layer nitrile coating (3/4 smooth + palm with sandy finish) is waterproof, and the long reinforcement between the thumb and index finger provides excellent grip and good handling in the most demanding dry and oily tasks, as well as a high level of abrasion protection (COVERPERF label: >20,000 cycles).

The CLAW CUT F 505 is made with recycled polyester fiber and certified RCS (16% of the total product weight). It contains no fiberglass.

This glove is touchscreen compatible, allowing you to keep it on while

Oily Environment



The +

- COVERPERF DURABILITY: ABRASION (exceptional wear resistance, >20,000 cycles) and WASHABILITY (performance guaranteed for up to 5 cycles at 30°) for maximum durability
- COVERPERF SKINCARE: Hypoallergenic to prevent irritation
- CUT F: Maximum cut protection level (EN388 standard)
- Gauge 18 without fiberglass: Comfort and high dexterity
- Double layer nitrile coating (3/4 smooth + palm sandy finish): Excellent grip in dry and oily environments, waterproof
- Long thumb-index reinforcement: Improved grip and prevents tearing for maximum durability
- RCS: Integration of recycled materials (16%) to reduce environmental impact
- HOT 1: Contact heat protection 100°C / 15 sec.
- Touchscreen, Sanitized

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CLF505006	6	10	100
1CLF505007	7	10	100
1CLF505008	8	10	100
1CLF505009	9	10	100
1CLF505010	10	10	100
1CLF505011	11	10	100
1CLF505012	12	10	100

TECHNICAL FEATURES



Gauge 18

Color	Black
Glove type	Seamless knitting
Coating level	3/4
Material of coating	Nitrile
Coating finition	Smooth
Coating level	Palm
Material of coating	Nitrile
Coating finition 2	Sandy
Reinforced part place	Between thumb and index finger
Reinforced part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0598/PPE/25/3577 Issue 1

Delivered by SGS Fimko Oy (0598) Takomotie 8 00380 HELSINKI Finland



EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



4.X.4.3.F.

ANSI

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15



EN407:2020

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)



X.1.X.X.X

EN16350:2014

Protective gloves - Electrostatic properties

COVERPERF -
Durability/Abrasion resistance



COVERPERF -
Durability/Washable



COVERPERF - Skincare
MAJ 03/04/2026