

Ref. 1CUPF00

Cut - Precision Work

Dry Environment



The +

Highest level of cut protection: CUT F
Dexterity
Crotch between thumb and index
Touchscreen
Heat protection 100°C / 15 sec.
Dirt resistant

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CUPF00007	7	10	100
1CUPF00008	8	10	100
1CUPF00009	9	10	100
1CUPF00010	10	10	100
1CUPF00011	11	10	100

SALES PACKAGING

Hangable individual polybag

DESCRIPTION

Grey seamless support from HDPE,
Black PU palm coating,
Nitrile crotch reinforcement between thumb and index,
Knitted wrist
Certified OEKO-TEX® STANDARD 100, CQ 1301/1, IFTH

SECTORS

- Light Industries
- Maintenance
- Services and distribution

APPLICATIONS

Handling in dry area with mechanical and thermal risks, for glass industry, automotive or aeronautical industries, injection moulding, construction, logistics,...

TECHNICAL FEATURES



Gauge 13

Color	Grey
Color 2	Black
Shape	Glove
Gloves environment	Dry environment
Glove type	Seamless knitting
Support material	HDPE polyester Elastane
Coating level	Palm
Material of coating	PU
Coating finition	Smooth
Reinforced part place	Between thumb and index finger
Reinforced part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/05/20/1556

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 21420:2020

+ A1:2024

EN388:2016

+ A1:2018



4.X.4.4.F.

ANSI



EN407:2020



X.1.X.X.X

Protective gloves – General requirements and test methods

Protection from mechanical risks

Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)