

Ref. 6PHW200

Vented Helmet General Use



The +

PERFORMANCE: High resistance (lateral deformation (LD), low temperatures -30°C) // ABS cap
COMFORT: Integrated safety glasses // Good balance and lightweight feel (450g) // Easy adjustment with ratchet // Preservation of viewing area thanks to the short visor // 3D textile lining
CUSTOMIZATION: Add your logo (optional, upon request)
 Compatible with helmet strap MO60705, badge holder (6POBA) and ear muffs (6MX3000NSI)

DESCRIPTION

PHOENIX WIND Safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, side ventings, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 points chinstrap as a standard

SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Regional/public authorities
- Infrastructure, building industry

APPLICATIONS

Construction site, building and public works, industry...

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHW200NSI	-		16

SALES PACKAGING



Individual polybag

See also

VARIANTS



6PHW400



6PHW160



6PHW800



6PHW170

TECHNICAL FEATURES

Shape	Safety helmet	Shell material	ABS
Color	Blue	Features	ABS Shell
Color 2	Black		LDPE 6 points harness
Weight	450g		Size adjustment from 52 to 63 cm
Shade	Clear	Service life	Manufacturing date indicated under the peak
Harness features	6 points harness made of polyethelene		Shelf life: Storage for 2 years in standard conditions
Main risk	6 textile webbings		Use for 5 years in good conditions
	Prevention from falling objects and head injuries or head trauma	Adjustment	Adjustment by ratchet from 52 to 63 cm

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2314

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



PPE CAT. II

EN397:2012 + A1:2012

Industrial safety helmets

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.